

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
7 April 2005 (07.04.2005)

PCT

(10) International Publication Number
WO 2005/030401 A1

(51) International Patent Classification⁷: **B05B 11/00**

(21) International Application Number:
PCT/GB2004/003790

(22) International Filing Date:
6 September 2004 (06.09.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
0322758.4 29 September 2003 (29.09.2003) GB

(71) Applicant (for all designated States except US): **BESPAK PLC** [GB/GB]; Blackhill Drive, Wolverton Mill South, Milton Keynes, Buckinghamshire MK12 5TS (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **WRIGHT, Andrew,**

David [GB/GB]; 5 Malthouse Close, Heacham, King's Lynn, Norfolk PE31 7EH (GB).


(74) Agents: **ILLINGWORTH-LAW, William et al.;** D. Young & Co., 120 Holborn, London EC1N 2DY (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PI, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: A DISPENSING APPARATUS



(57) Abstract: A hand-held multi-dose dispensing apparatus (10) comprising a metering chamber (20) having an axis (21), an end portion (22) at one axial end of the chamber (20) and a side body portion (23) extending from the axial end portion (22), a piston arrangement (30) movable with a piston stroke along the axis of the metering chamber (20) with a seal portion (34) of the piston arrangement (30) being slidably engageable with an inside surface of a side portion (23) of the metering chamber, an inlet (27) for fluid to enter the metering chamber (20), and an outlet (31, 32) for fluid to be dispensed from the metering chamber (20), wherein the inlet (27) is provided on the side body portion (23) of the metering chamber and, in use, during a first portion of the piston stroke, the inlet (27) is in fluid communication with the metering chamber (20) and during a second portion of the piston stroke, the seal portion (34) of the piston arrangement (30) blocks the inlet (27) preventing fluid from passing from the inlet (27) into the metering chamber (20). This dispensing apparatus (10) reduces variations in the shot weight dispensed, by the metering of the fluid commencing at the point at which the piston enters the second portion of its stroke blocking off the inlet.



European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— with international search report